DEPENDENT RESURVEY OF SUBDIVISION OF T. 45 N., R. 32 E.

. •	Chains	No timber; undergrowth, sagebrush. Grazing, fair.
		N. 1° 11' E., bet. secs. 3 and 4.
		Asc. 90 ft. over W. slope.
	9.50	Divide between Deep Creek and Bilk Creek, bears S. 70° E., and N. 70° W.; desc. 240 ft. over NE. slope.
	20.25	Slope changes; desc. 100 ft. over N. slope.
	25.20	Wash, course NE.; along E. slope.
	30.00	Spur, slopes NE.; desc. 300 ft. over N. slope.
	40.01	Proportionate distance,
		Set an iron post, 3 ft. long, I in. diam., 27 ins. in the ground, for \(\frac{1}{4} \) sec. cor., with brass cap mkd.
		1 1
		1938
		raise a mound
		of stone, 2 ft. base, 1 ft. high, W. of cor.
	42.00	Wash, course NE.; asc. 70 ft. along E. slope.
	57-50	Spur, slopes E.; desc. 160 ft. over NE. slope.
	67.20	Bilk Creek, 10 lks. wide, 6 ins. deep, course S. 60° E.; asc. 280 ft. over SW. slope.
	80.52	Intersect the 9th Standard Parallel North at the point for the reestablished closing cor. of secs. 3 and 4.
		Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for closing cor. of secs. 3 and 4, with brass cap mkd.
		т46n s 34
u		S4 S3 T45N R32E
IN HE KI		CC
		1938 raise a mound
		of stone, 2 ft. base, $1\frac{1}{3}$ ft. high, S. of cor.
	•	This corner is reestablished at record bearing and distance, East, 10.62 chs. dist., from the standard cor. of secs. 33 and 34, the nearest identified original corner to the west on the 9th Standard Parallel North.
	٠	From this corner, the standard corner of lots 7 and 8, on the S. bdy. of sec. 34, an iron post, 1 in. diam., set, mkd. and witnessed as described in the field notes of the survey of T. 46 N., R. 32 E., bears West, 0.36 chs. dist.
		From the same point, the standard $\frac{1}{4}$ sec. cor., on the S. bdy. of sec. 34, an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record, bears East, 39.64 chs. dist.
H		Land, mountainous. Soil, rocky; 4th rate. No timber; undergrowth, sagebrush. Grazing, fairly good.