## SUBDIVISION OF PORTION OF T. 45 N., R. 32 E.

	Chains	P. La Z. C. S.
		vision design and the second and the
	, have $\tau_{c}$	1938 raise a mound
		of stone, 2 ft. base, la ft. high, W. of cor.
-	46.20	Wash, course East, along E. slope.
	50.80	Desc. 250 ft. over NE. slope.
	57.70	Wash, course N. 70° E.; asc. 70 ft. over SE. slope.
	63.00	Along E. slope.
	74.00	Desc. 140 ft. over NE. slope.
	79.00	Spring, bears East, 0.50 chs. dist.
	79.90	Sidehill drain, course East, along E. slope.
	80.00	Set an iron post, 3 ft. long; 1 in. diam., 27 ins. in the ground, for cor. of lots 5 and 12, sec. 1 and lots 8 and 9, sec. 2, with brass cap mkd. $ S = 2^{S} \frac{8}{9} \frac{5}{12} S 1 $
		1938
	94.50	Soll, reserved the rate.
	101.80	Wash, course N. 70° E., over rolling land.
	108.86	Intersect 9th Standard Parallel North.
		Set an iron post, 3 ft. long, 2 ins. diam.; 27 ins. in the ground, for closing cor. of secs. 1 and 2, with brass cap mkd.  T46N R32E S35
,	minto	S 2 S 1 T45N R32E CC 1938
		raise a mound
		of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of cor.  The standard cor. of secs. 35 and 36, an iron post, 2 ins. diam.,
		set, mkd. and witnessed as described in the official record, bears East, 0.77 chs. dist.
. N:	And the second s	The standard & sec. cor. of sec. 35, an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record, bears West, 39.23 chs. dist.
		Land, mountainous and rolling. Soil, rocky and gravelly, 3rd and 4th rate. Timber, none. Undergrowth, sagebrush. Grazing, good.
	N 495 3	From the cor. of secs. 33 and 34, on the S. bdy. of the tp., an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record.
	•	North, along sectional guide meridian bet. secs. 33 and 34.
		Over rolling land, draining generally west.
	1	