

SUBDIVISION OF PORTION OF T. 45 N., R. 32 E.

Chains

S 20  
 $\frac{1}{4}$  ———  
 S 29  
 1938

Asc. 50 ft. over E. slope.

48.00 Spur, projects S. 20° E.; desc. 30 ft. over W. slope.

54.00 Drain, course SE.; asc. 350 ft. over E. slope.

78.00 Top of steep ascent, across top of ridge, bears S. 30° E. and N. 30° W.

79.90 The cor. of secs. 19, 20, 29 and 30.

Land, rolling mountainous.  
 Soil, rocky, 4th rate.  
 Timber, none.  
 Undergrowth, sagebrush.  
 Grazing, poor.

West, bet. secs. 19 and 30.

Across top of ridge, bears S. 30° E. and N. 30° W.

2.20 Desc. 340 ft. over SW. slope.

26.60 Head of wash, course S. 10° E.; asc. 110 ft. over E. slope.

36.50 Ridge, bears S. and slopes sharply to saddle about N. 70° E. 12.00 chs. dist. Desc. 75 ft. over W. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S 19  
 $\frac{1}{4}$  ———  
 S 30  
 1938

raise a mound

of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, N. of cor.

Desc. 350 ft. over W. slope changing to general N.W. slope.

79.82 Intersect E. bdy. T. 45 N., R. 31 E.

Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground, to bedrock, and in a mound of stone to top, with a basalt stone, 6x6x3 ins., mkd. X, deposited at base, for closing cor. of secs. 19 and 30, with brass cap mkd.

T45N  
 R31E R32E  
 S25 | S19 — CC  
 | S30  
 1939

The cor. of secs. 24 and 25 bears N. 1° 31' E. 3.40 chs. dist.

Land, mountainous and rolling.  
 Soil, rocky, 3rd and 4th rate.  
 Timber, none.  
 Undergrowth, sagebrush.  
 Grazing, fair.