

SUBDIVISION OF PORTION OF T. 45 N., R. 32 E.

Chains

of stone, 2 ft. base, 1 1/2 ft. high, N. of cor. raise a mound

Desc. 130 ft. over W. slope.

45.00 Wash, course S. 5° E.; asc. 410 ft. over broken E. slope.

67.30 Ridge, bears S. 20° E. and North; desc. 200 ft. over W. slope.

79.15 Intersect E. bdy. T. 45 N., R. 31 E.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for closing cor. of secs. 6 and 7 with brass cap mkd.

T45N	T45N
R31E	R32E
S12	S 6
	CC
	S 7

1939

of stone, 2 ft. base, 1 1/2 ft. high, E. of cor. raise a mound

The cor. of secs. 1 and 12, T. 45 N., R. 31 E., bears N. 0° 24' E., 3.31 chs. dist.

Land, mountainous.
Soil, rocky; 3rd rate.
Timber, none.
Undergrowth, sagebrush.
Grazing, fair.

At midpoint on the W. bdy. of Sec. 7,

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for 1/4 sec. cor. of sec. 7 only, with brass cap mkd.

1/4 S 7

1939

stone, 3 ft. base, 2 ft. high, E. of cor. raise a mound of

The 1/4 sec. cor. of sec. 12, T. 45 N., R. 31 E., a 1 in. iron post, bears N. 0° 24' E., 3.47 chs. dist.

At point on W. bdy. of sec. 6, 40.00 chs. in latitude from the SW. cor. thereof,

Set an iron post, 3 ft. long, 1 in. diam., 9 ins. in the ground, to solid rock with a basalt rock, 4x4x5 ins., mkd. X deposited at the base, and in a large supporting mound of stone, for 1/4 sec. cor. of sec. 6 only, with brass cap mkd.

1/4 S 6

1939

The 1/4 sec. cor. of sec. 1, T. 45 N., R. 31 E., a 1 in. iron post, bears N. 0° 24' E., 3.12 chs. dist.

From the cor. of secs. 5, 6, 7 and 8.

N. 0° 02' W., bet. secs. 5 and 6.