SUBDIVISION OF PORTION OF T. 45 N., R. 32 E.

Chains	Asc. 40 ft. over S. slope.
4.20	Spur, slopes E.; desc. 130 ft. over N. slope.
15.30	Wash, course E.
17.50	Wash, course SE.: asc. 100 ft. over S. slope.
26,00	Spur, slopes S. 70° E.; desc. 60 ft. over NE. slope.
29•00	Wash, course S. 70° E.; asc. 160 ft. over SW. slope, changing to W. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for \(\frac{1}{4} \) sec. cor., with brass cap mkd.
	s6 s5
	1938 raise a mound
	of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
	Asc. slightly along W. slope.
42.00	Desc. 20 ft. along W. slope.
47.00	Asc. 200 ft. along W. slope.
61.00	Sidehill wash, course S. 30° W.; asc. 400 ft. over general SW. slope.
80.00	Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, to bedrock, with a lava stone 6x4x1 in. mkd. X, deposited at base, and in a mound of stone to top for cor. of lots 5 and 12 sec. 5 and lots 15 and 16, sec. 6, with brass cap mkd.
	s6 15 5 s5 16 12 1938
	Asc. 260 ft. along W. slope.
100.60	Divide bet. Bilk Creek and Deep Creek bears NW. and SE., desc. 110 ft. over N. to NE. slope.
108.83	Intersect 9th Stan. Par. N.
	Set an iron post, 3 ft. long, 2 ins., diam., 27 ins. in the ground, for closing cor. of secs. 5 and 6, with brass cap mkd.
	T46N· R32E-
	S32 S6 S5 T45N R32E
	CC 1938
	of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of cor. raise a mound
	The cor. of secs. 31 and 32, T. 46 N., R. 32 E., a 2 in. iron post, bears West, 0.43 chs. dist.
	Land, mountainous. Soil, rocky: 3rd rate. Timber, none. Undergrowth, sage brush. Grazing, fairly good.

Establishment of 1/4 sec. corners on the 9th Standard Parallel North