

## 9TH STANDARD PARALLEL NORTH THRU RANGE 32 EAST

Chains

SC  
~~1835~~

1937

raise a mound

of stone, 2 ft. base, 1½ ft. high, N. of cor.

- 40.30 Draw, drains S. 30° E.; asc. 680 ft. over precipitous slope.
- 61.00 Divide between Skull and Bilk Creeks, bears N. 10° W., and S. 10° E.; desc. 20 ft. along southerly slope.
- 67.00 Swale, drains S.; asc. 200 ft. over southeasterly slope.
- 79.40 Spur, slopes S. 5° W.;
- 80.00 S. 3 lks. from the secant

Set an iron post, 3 ft. long, 2 ins. diam., 15 ins. in the ground to underlying rock, with a volcanic stone, 8x6x4 ins., mkd. X, deposited at base, and in mound of stone to top, for standard cor. of secs. 34 and 35, with brass cap mkd.

SC  
 T46NR32E  
 S34 | S35  
 1937

Land, rough mountainous  
 Soil, rocky, 4th rate.  
 No timber; undergrowth, sagebrush and rabbit brush  
 Grazing, poor.

The resurvey of the remainder of the 9th Standard Parallel North thru R. 32 E., is in accordance with instructions contained in District Cadastral Engineer's letter dated August 10, 1937, approved by telegram dated August 20, 1937, from the Commissioner of the General Land Office.

Independent Resurvey of a portion of the S. bdy. of T. 46 N., R. 32 E. superseding the survey executed by G. W. Garside & C. S. Preble, U. S. Deputy Surveyors, in 1875 under contract No. 67.

West, along the S. bdy. of sec. 34, continuing the transit line establishing the standard parallel which bears N. 89°59.3' W., and starts from a point 3 lks. north of the standard cor. of secs. 34 and 35.

Desc. 440 ft. over very rocky SW. slope.

- 20.00 Drain, near head, course S. 10° W.; asc. 100 ft. over southeasterly slope.
- 24.80 Along S. slope.
- 31.80 Spur, slopes SW.; desc. 260 ft. over westerly slope.
- 40.00 S. 3 lks. from the secant.

Set an iron post, 3 ft. long, 1 in. diam., 15 ins. in the ground to underlying rock, with a volcanic stone, 8x6x2 ins. mkd. X, deposited at base, and in a mound of