E. BDY. T. 46 N., R. 32 E.

| | Chains | $\frac{1}{4}$ |
|--|--------|---|
| | | 1915 raise a mound |
| | | of stone, 2 ft. base, $l^{\frac{1}{2}}$ ft. E. of cor. and destroy the mound of stone, W. of cor. |
| | 60.32 | The cor. of Tps. 46 and 47 N., R. 32 E., only, an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record. |
| | | Land, rolling, Soil, gravelly and rocky; 4th rate. No timber; no undergrowth. Grazing, fair. |
| 11 | | RESURVEY OF THE S. BDY. OF T. 47 N., R. 32 E. |
| • | | Supplementing the survey by Walter E. Hoffman, U. S. Surveyor, in 1915, under Group No. 35. |
| | | This resurvey was made to establish iron post monuments at the corner points referring to this township. A new record as to topographic and other features is not reported. |
| | | West, along the S. bdy. of sec. 36. |
| | 39.74 | The $\frac{1}{4}$ sec. cor., an iron post, l in. diam., set, mkd. and witnessed as described in the official record. |
| | | As this now becomes the $\frac{1}{4}$ sec. cor. of sec. 36 only, I remark the brass cap to read as follows, |
| | | 1 4S36 |
| 0.0000 | * * * | 1915 |
| THE CONTRACTOR STATES | 40.53 | A point 40.00 chs. in departure from the closing cor. of secs. 1 and 2. |
| | 4-3 | Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for \(\frac{1}{4} \) sec. cor., with brass cap mkd. |
| | | <u></u> <u>‡</u> S1 |
| | | 1937 raise a mound |
| 50 miles (100 miles) | | of stone, 2 ft. base, $l^{\frac{1}{2}}$ ft. high, S. of cor. |
| The state of the s | 79•74 | The cor. of secs. 1, 2, 35 and 36, an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record. |
| | | As this now becomes the cor. of secs. 35 and 36, T. 47 N. R. 32 E., only, I remark the brass cap to read as follows, |
| | | T47N R32E S35 S36 S S1 T46N |
| | | 1915 |
| | | |