

RESURVEY OF S. BDY. T. 47 N., R. 32 E.

Chains

raise a mound

of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of cor.

41.705 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

 $\frac{1}{4}$ S31

1938

raise a mound

of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.63.50 Spur, slopes S. 70° W.; desc. 600 ft. over W. slope.

81.42 A point 80.00 chs. in departure from the closing cor. of secs. 5 and 6.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for cor. of lots 4 and 5, sec. 6, with brass cap mkd.

 $\frac{5}{56}$ 4

1938

raise a mound

of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of cor.

82.735 The SW. cor. of T. 47 N., R. 32 E., an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record.

Land, rough mountainous.

Soil, rocky; 4th rate.

No timber; undergrowth, sagebrush;

Grazing, fair.

Dependent Resurvey of the E. Bdy., T. 46 N., R. 31 E. Reestablishing the survey executed by Walter H. Good, U. S. Transitman, in 1923.

This resurvey is made for the purpose of establishing corners for T. 46 N., R. 32 E., and for altering the corner marking for T. 46 N., R. 31 E., also for obtaining the correct alinement. No topographic entries are made, except on E. bdy. sec. 1.

Beginning at the standard cor. of T. 46 N., Rs. 31 and 32 E., an iron post, 3 ins. diam., set, mkd. and witnessed as described in the original record.

As this now becomes the cor. for T. 46 N., R. 31 E., only, I remark the brass cap to read as follows,

SC
T46N
R31E
S36

1923