

Township 26 N., Range 26 East.

Chains

Survey commenced August 7, 1938, For detailed description of instruments, establishment of meridian and determination of azimuth, and data pertaining to measurements, refer to the field notes of T. 26 N., R. 25 E., surveyed under this group.

SURVEY OF THE NORTH BOUNDARY OF T. 26 N., R. 26 E.

The cor. of Ts. 26 and 27 N., R. 26 E., as established by W. A. Pray, U.S. Surveyor in 1911 under Group 13 Nevada, is an iron post, 3 ins. diam., 12 ins. above ground, firmly set, marked and witnessed as described in the official record. As this corner under the present survey will not refer to R. 26 E., I obliterate the markings on the brass cap and remark same for a Reference Point as follows:

RP

1938

The closing cor. of Ts. 26 and 27 N., R. 27 E., as established by W. A. Pray, U. S. Surveyor under Group 13 Nevada, is a basalt rock, 24x10x6 ins., showing 8 ins. above the ground, firmly set, marked and witnessed as described in the official record. This now becomes the corner of Ts. 26 and 27 N., Rs. 26 and 27 E.

At point for corner,

Set an iron post, 3 ft. long, 3 ins. diam., 28 ins. in the ground, with the original stone deposited at the base, for the cor. of Ts. 26 and 27 N., Rs. 26 and 27 E., with brass cap mkd:

T27N
R26E R27E
S 36 | S 31
S 1 | S 6
T26N
1938

from which

The Reference Point, above described, bears South 3.15 chs. dist.

From the cor. of Ts. 26 and 27 N., Rs. 26 and 27 E.

S. 89° 53' W., on true line, along the N. bdy. of T. 26 N., R. 26 E., between secs. 1 and 36.

Over slightly rolling land thru medium dense low undergrowth.

35.60 Small drain, course S. 70° E.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a granite rock 7x6x2 ins., mkd. X, deposited at the base of post, for 1/4 sec. cor., with brass cap mkd.

S 36
1/4
S 1

1938

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 1, 2, 35 and 36, with brass cap mkd.