

SURVEY OF THE SOUTH BOUNDARY OF T. 30 N., R. 27 E., M.D.M., NEVADA

Chains

The survey of the S. bdy. of T. 30 N., R. 27 E., M.D.M., Nevada was executed by James W. Hardison on October 27, 1938. For description and test of instruments, method of measurements and determination and verification of azimuth refer to the field notes of T. 29 N., R. 26 E., M.D.M., executed under this same group.

Beginning at the corner of Ts. 29 and 30 N., Rs. 27 and 28 E., which is monumented with an iron post, 3 ins. diam., firmly set, marked and witnessed as described in the official record.

West, along the S. bdy. of sec. 36, T. 30 N., R. 27 E., on a transit line describing the secant, which starts from a point 4 lks. S. of the Tp. cor., and bears N. 89° 57.8' W.

Over gently rolling land, through scattering undergrowth.

- 9.40 Wash, course S. 10° W.
 33.80 Wash, course S. 30° W.
 40.00 Point for the $\frac{1}{4}$ sec. cor. of sec. 36, N. 2 lks. from the secant.
 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ S 36

1938

raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

- 70.40 Wash, course SW.
 79.40 Wash, course S. 35° W.
 80.00 Point for the cor. of secs. 35 and 36, on the secant.
 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with brass cap mkd.

T30N | R27E

S35 | S36

T29N | R27E

S2

raise a mound of stone, 2 ft. base, ¹⁹³⁸ $1\frac{1}{2}$ ft. high, N. of cor.

Land, gently rolling.
 Soil, gravelly; 3rd rate.
 Timber, none.

West along the S. bdy. of sec. 35, on a transit line describing the secant, which bears N. 89° 58.5' W.

Over gently rolling land through scattering undergrowth.

- 4.80 Wash, from NE., course S. for 5 chs. then SW.
 16.80 Wash, course S. 15° W.
 40.00 Point for the $\frac{1}{4}$ sec. cor. of sec. 35, S. $1\frac{1}{2}$ lks. from the secant.
 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ S 35

1938