

Subdivision of T. 30 N., R. 27 E.

Chains

Beginning the subdivisional survey at the corner of secs. 35 and 36, on the S. bdy. of the Tp., which is monumented with an iron post, 2 ins. diam., marked and witnessed as described in the 1938 survey record.

N. 0° 05' E., bet. secs. 35 and 36.

Over rolling and broken land, through scattering undergrowth.

16.40 Channel of wash, 10 lks. wide, 2 ft. deep, course SW.

28.30 Dim old road trail, bears N. 60° W. and S. 60° E.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ S35 \mid S36 \\ 1949 \end{array}$$

raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

45.40 Channel of wash, 10 lks. wide, 2 ft. deep, course S. 70° W.

80.00 Point for the cor. of secs. 25, 26, 35, and 36.

Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock and in a mound of stone to top, with brass cap mkd.

$$\begin{array}{c} T30N \ R27E \\ S26 \mid S25 \\ \hline S35 \mid S36 \\ 1949 \end{array}$$

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, rolling.

Soil, silt, sandy and rocky; with gravel benches.

No timber; undergrowth, shadscale, sage and greasewood.

Grazing, poor.

From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., which is monumented by an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the 1927 survey record.

S. 89° 59' W., bet. secs. 25 and 36.

Over rolling land, through scattering undergrowth.

30.70 Channel of wash, 10 lks. wide, course S. 30° W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} S \ 25 \\ \frac{1}{4} \hline S \ 36 \\ 1949 \end{array}$$

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.