

Subdivision of T. 30 N., R. 27 E.

Chains	
37.90	Wash, 30 lks. wide, $2\frac{1}{2}$ ft. deep, course SW.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 11. Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
	$\begin{array}{r} S \ 2 \\ \frac{1}{4} \text{ ---} \\ S \ 11 \\ 1949 \end{array}$
	raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, N. of cor. Desc. 55 ft. over gentle SW. slope to edge of bench.
42.00	Road, bears N. 55° E. and S. 55° W.
64.00	Edge of bench, bears NE. and SW.; desc. 30 ft.
73.40	Wash, 30 lks. wide, 1 ft. deep, course SW.
77.00	Main wash, 50 lks. wide, 4 ft. deep, course SW. winding; asc. 25 ft.
78.50	Edge of bench, bears N. and S.; desc. slightly.
80.00	The cor. of secs. 2, 3, 10, and 11. Land, rolling. Soil, sandy gravelly and rocky; 4th rate. No timber; undergrowth, sage, and desert brush. Grazing, fair.
	N. 0° $04'$ E., bet. secs. 2 and 3. Over rolling land, through undergrowth, along a broken edge of bluff bearing N. 10° W. and S. 10° E.
12.50	Edge of bluff, bears N. 10° E. and S. 10° W.; thence asc. gradually along edge of bluff 30 ft.
27.50	Desc. 15 ft. along edge of bluff.
39.80	Road, bears N. 10° E. and S. 10° W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.
	$\begin{array}{r} \frac{1}{4} \\ S \ 3 \ \ S \ 2 \\ 1949 \end{array}$
	raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.
47.52	Intersect the Sixth Standard Parallel North. Point for the closing cor. of secs. 2 and 3. Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.