Subdivision of T. 30 N., R. 27 E.

S. Commission		
N	Chains 3.90	Road, bears N. and S.
	27.40	Wash, 10 lks. wide, 2 ft. deep, course SW.
	39.98	Point for the 4 sec. cor. of secs. 3 and 10.
•	*	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.
	- 1 w	s 3
		1/4
		s 10 1949
		raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, N. of cor.
	42.10	Old trail road, bears N. and S.
	69•70	Wash, 10 lks. wide, $2\frac{1}{2}$ ft. deep, course SW.; asc. 30 ft. over SE. slope.
	79•96	The cor. of secs. 3, 4, 9, and 10.
		Land, rolling.
		Soil, sandy, gravelly and lava ash with rocks strewn over the surface; 4th rate.
	*	No timber; undergrowth, sage, shadscale and desert brush. Grazing, fair.
	on of	
		N. 0° 04' E., bet. secs. 3 and 4.
		Over rolling land, through dense undergrowth; asc. over a gentle SE. slope.
	30.00	Slope changes to a S. slope; asc. 30 ft.
	40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4.
		Set an iron post; 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
		<u>1</u>
		s 4 s 3
		1949
		raise a mound of stone, 31 ft. base, 3 ft. high, W. of cor.
	42.10	Wash, 10 lks. wide, course S. 80° E.
	47•53	Intersect the Sixth Standard Parallel North.
		Point for the closing cor. of secs. 3 and 4.
	e	Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.
		T31N R27E
		S 1 ₁ S 3
		T30N R27E
	g.	CC 1949
	*	raise a mound of stone, 3 ft. base, 3 ft. high, S. of cor.