

Subdivision of T. 30 N., R. 27 E.

Chains

West, bet. secs. 4 and 9.

Asc. gradually 105 ft. over a broken SE. slope, through dense undergrowth.

11.60 Wash, 20 lks. wide, 2 ft. deep, course SE.

39.98 Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 9.

Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground to bedrock and in a mound of stone, 4 ft. base to top, with brass cap mkd.

$$\begin{array}{c} S \ 4 \\ \frac{1}{4} \text{---} \\ S \ 9 \\ 1949 \end{array}$$
raise a mound of stone, $3\frac{1}{2}$ ft. base, 3 ft. high, N. of cor.

Asc. gradually 145 ft. over a broken and rocky SE. slope.

49.70 Wash, 20 lks. wide, $2\frac{1}{2}$ ft. deep, course SE.

75.50 Wash, 10 lks. wide, 6 ft. deep, course SE.

79.96 The cor. of secs. 4, 5, 8, and 9.

Land, rolling, and broken.

Soil, sandy, volcanic ash, gravelly and very rocky; 4th rate.

No timber; undergrowth, shadscale, sage, and desert brush.

Grazing, fair.

N. $0^{\circ} 03'$ E., bet. secs. 4 and 5.

Over rolling and broken SE. slope, asc. gradually 120 ft. through dense undergrowth.

4.50 Wash, 10 lks. wide, 6 ft. deep, course SE.

18.90 Wash, 20 lks. wide, 6 ft. deep, course SE.

31.90 Wash, 20 lks. wide, $2\frac{1}{2}$ ft. deep, course SE.40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ S \ 5 \ | \ S \ 4 \\ 1949 \end{array}$$
raise a mound of stone, $3\frac{1}{2}$ ft. base, 3 ft. high, W. of cor.

40.30 Wash, 10 lks. wide, 3 ft. deep, course SE. winding; asc. 30 ft. over SE. slope.

43.60 Wash, 10 lks. wide, $2\frac{1}{2}$ ft. deep, course SE.

47.00 Wash, 5 lks. wide, 2 ft. deep, course SE.

47.50 Intersect the Sixth Standard Parallel North.