· Subdivision of T. 30 N., R. 27 E.

Chains

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\frac{1}{4}$$

s 6 | s 5

raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.

Asc. 160 ft. over a rocky SE. slope.

47.43

Intersect the Sixth Standard Parallel North.

Point for the closing cor. of secs. 5 and 6.

Set an iron post, 3 ft. long, 2 ins. diem., 6 ins. in the ground to bedrock and in a mound of stone, 5 ft. base to top, with brass cap mkd.

raise a mound of stone, 4 ft. base, 3 ft. high, S. of cor.

From the point of intersection the standard cor. of secs. 31 and 32, T. 31 N., R. 27 E., bears West, 2.38 chs. dist., and is monumented with an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the record of the 1947 resurvey of the Sixth Standard Parallel North, through R. 27 E.

From the same point the standard $\frac{1}{4}$ sec. cor., S. bdy. sec. 32, T. 31 N., R. 27 E., bears East, 37.62 chs. dist., and is monumented with an iron post, 1 in. diam., firmly set, mkd. and witnessed as described in the record of the 1947 resurvey of the Sixth Stan. Par. N., through R. 27 E.

Land, rough rugged mountainous.
Soil, sandy and rocky; 4th rate.
No timber; undergrowth, sagebrush and desert brush.
Grazing, fair.

Note:

On each mile along the north boundary of the township, which is the Sixth Stan. Par. N., through R. 27 E., new $\frac{1}{4}$ sec. cors. of minimum control for the sections of T. 30 N., R. 27 E., are established; the positions are determined by proportionate measurements as based upon the representations of the 1947 resurvey.

The point of the $\frac{1}{4}$ sec. cor. of sec. 1 on the N. bdy. of the Tp., is at midpoint, on the N. bdy. of the Tp.

At the corner point,

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.