

Independent Resurvey of 6th Stan. Par. N. thru R. 27 E.

Chains

Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the ground and in a mound of stone, 6 ft. base, to top, with brass cap mkd.

SC
T31N | R27E
S31 | S32

1947

from which

A slate rock in place, 5x3x2 ft., bears N. 10° 08' E., 1.00 ch. dist. mkd. XBO 32.

A slate rock in place, 6x4x3 ft., bears N. 51 $\frac{1}{2}$ ° W., 28 lks. dist., mkd. XBO 31.

From this corner the original standard corner of secs. 31 and 32, bears N. 15° 36' E., 3.76 chs. dist., mkd. by the original monument, a slate stone, 12x10x8 ins., mkd. as described in the official record. Destroy all evidence of this corner.

Land, mountainous.

Soil, gravelly to rocky, slate, shale, schist and quartz.

Undergrowth, shadscale and sagebrush.

West, along the S. bdy. of sec. 31, on a transit line describing the tangent, which bears S. 89° 56.4' W.

Ascend 70 ft. over SE. slope.

- 5.00 Top of main ridge, bears N. 20° E. and S. 20° W.; desc. 250 ft. over general W. slope of mountain.
- 19.20 Top of spur, slopes S. 60° W.; desc. 140 ft. over NW. slope.
- 26.10 Head of ravine, course NW.; desc. 210 ft. over N. slope.
- 40.00 Point for the standard $\frac{1}{4}$ sec. cor. of sec. 31, N. 26 $\frac{1}{2}$ lks. from the tangent.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

SC
 $\frac{1}{4}$ S 31

1947

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

From this cor. the original standard $\frac{1}{4}$ sec. cor. of sec. 31 bears N. 22° 06' E., 3.30 chs. dist., mkd. by the original monument, a slate stone, 14x14x4 ins. mkd. and witnessed as described in the official record. Destroy all evidence of this corner.

Asc. slightly along N. slope.

- 42.50 Spur slopes NW.; desc. 520 ft. over W. slope.
- 80.00 Point for the standard cor. of Ts. 31 N., Rs. 26 and 27 E., N. 31 links from the tangent.
- Set an iron post, 3 ft. long, 3 ins. diam., 30 ins. in the ground, with brass cap mkd.