

East Boundary of T. 29 N., R. 27 E.

Chains

Set an iron post, 3 ft. long, 1 in. diam., 4 ins. in the ground to bedrock and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

$\frac{1}{4}$
 S12 | S 7
 1949

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Asc. 10 ft. over S. slope.

42.50 Top of small oblong knoll, bears E. and W.; desc. 35 ft. over a N. slope.

46.70 Foot of slope; thence over a lava and boulder strewn plain; ascend slightly.

59.80 Wash, 20 lks. wide, course SW.

63.25 Unimproved road, bears N. 30° E. to Porter Spring and winding southwesterly to main road.

80.00 Point for the cor. of secs. 1, 6, 7, and 12.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T 29 N
 R27E R28E
 S 1 | S 6
 S12 | S 7
 1949

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, rolling and hilly.

Soil, sandy, gravelly, and rocky; 4th rate.

No timber; undergrowth, sage, shadscale and desert brush.

North, bet. secs. 1 and 6.

Over lava and boulder strewn area, through scattering undergrowth; asc. slightly over rolling land.

7.30 Wash, 30 lks. wide, course SW.

10.80 Unimproved old trail road, bears E. and W.

12.60 Wash, 15 lks. wide, course SW. winding.

16.60 Winding wash, 25 lks. wide, course SW.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6.

Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground to bedrock and in a mound of stone to top, with brass cap mkd.

$\frac{1}{4}$
 S 1 | S 6
 1949