

Subdivision of T. 29 N., R. 27 E.

Chains

$$\begin{array}{r} S \quad 4 \\ \frac{1}{4} \text{ ---} \\ S \quad 9 \\ 1949 \end{array}$$

raise a mound of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, N. of cor.

Desc. 10 ft. over a general broken N. slope.

44.50 Wash, 30 lks. wide, 2 ft. deep, course N. 40° W.; thence asc. gradually 45 ft. to sec. cor.

64.90 Wash, 10 lks. wide, 6 inches deep, course NE.

79.98 The cor. of secs. 4, 5, 8, and 9.

Land, rolling and broken hills.

Soil, sandy, gravelly and rocky; 4th rate.

No timber; undergrowth, sage, shadscale and desert brush.

N. $0^\circ 03'$ W., bet. secs. 4 and 5.

Over rolling and broken hills, along a general NE. slope, through dense undergrowth, desc. 30 ft.

8.20 Wash, 5 lks. wide, 6 inches deep, course NE.; desc. 30 ft.

24.60 Unimproved dirt road, bears E. and W.; asc. 20 ft.

30.00 Point of spur, projects NE.; desc. 10 ft.

34.20 Main wash, 10 lks. wide, 2 ft. deep, course NE.; asc. 55 ft.

40.00 Top of round spur, projects SW.

Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \frac{1}{4} \\ S \quad 5 \quad | \quad S \quad 4 \\ 1949 \end{array}$$

raise a mound of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, W. of cor.

Desc. 45 ft. over a NW. slope.

54.10 Gulch, course winding SW.; asc. 65 ft. over a S. slope.

63.10 Point of spur, projects S. 80° E.; desc. 20 ft.

72.20 Wash, 5 lks. wide, 1 ft. deep, course SE.; asc. 50 ft.

78.43 Intersect the South Boundary of T. 30 N., R. 27 E.

Point for the closing cor. of secs. 4 and 5, T. 29 N., R. 27 E.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.