

18.  
294

Resurvey, Subdivision of T. 40 N., R. 27 E.

Chains	
	Dig a circular trench, 3 ft. diam., and raise a flat mound of earth and stone, 3 ft. base, around post.
	North, bet. secs. 2 and 3. (N½ mile)
	Along gentle E. slope, thru sagebrush.
8.70	Scraped road, not in use, bears NW. and SE.
33.05	Intersect the Eighth Standard Parallel North. Point for the closing cor. of secs. 2 and 3. Set an iron post, 30 ins. long, 2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T41N R27E S 34 S 31 S 2 T40N R27E C C 1951
	Dig a circular trench, 5 ft. diam., and raise a flat mound of stone, 2 ft. base, around post.
	From point of intersection the stan. cor. of secs. 34 and 35 bears east, 13.70 chs. dist.
	Land, nearly level, general easterly drainage. Soil, alkaline clayloam, 2d rate. Undergrowth, sagebrush.
	-----
	At the point for ¼ sec. cor. on N. bdy. of sec. 2, mid-distance in departure between the NE. and NW. cors.
	Set an iron post, 30 ins. long, 2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	1/4 S 2 1951
	Dig a circular trench, 5 ft. diam., around post.
	From this point the standard ¼ sec. cor., S. bdy. sec. 35, T.41 N., R.27 E., bears east, 8.94 chs. dist.
	-----
	From the cor. of secs. 10,11,14 and 15.
	S.89°07'W., bet. secs. 10 and 15.
	Ascend 95 ft. on rolling SE. slope, thru sagebrush.
22.40	Rimrock ledge, bears N. and S., on low ridge bearing E. and W.; descend 80 ft. on SW. slope.
25.30	Foot of slope, bears N. and S.; continue over nearly level land.
41.72	Point for the ¼ sec. cor. of secs. 10 and 15, at proportionate distance. Find no evidence of the original cor.
	Set an iron post, 30 ins. long, 2 ins. diam., 26 ins. in the ground, with brass cap mkd.