

## Subdivision of T. 40 N., R. 27 E.

## Chains

The point for  $\frac{1}{4}$  sec. cor. on N. bdy. of sec. 4 is 40.00 chs. W. of the NE. cor. of sec. 4.

As this point falls on an inaccessible position on a boulder, 20x12x5 ft. above ground, at point for a witness cor.  $\frac{1}{4}$  sec. 4, 30 lks. W. of true point

Set an iron post, 30 ins. long, 2 ins. diam., 26 ins. in the ground, with brass cap mkd.

$\xrightarrow{\text{WC}}$   
 $\frac{1}{4} \text{ S } 4$   
 1951

Raise a flat mound of stone, 3 ft. base, around post to top.

From true point for  $\frac{1}{4}$  sec. cor., the stand.  $\frac{1}{4}$  sec. cor., S. bdy. of sec. 33, T.41 N., R.27 E., bears E., 16.02 chs. dist.

-----  
 T. 40 N., R. 28 E.  
 -----

From the cor. of secs. 19,24,25 and 30, on W. bdy. of T.40 N., R.28 E.

The  $\frac{1}{4}$  sec. cor. of secs. 19 and 30 bears S.79°16'E., 44.69 chs. dist., evidenced by a mound of earth between pits to N. and S. Lying on the mound is a poplar stake, 18 ins. long, 1 in. diam., smoothed on one side and pointed on one end.

At the corner point

Set an iron post, 30 ins. long, 2 ins. diam., 26 ins. in the ground, with brass cap mkd.

$\frac{1}{4} \frac{\text{S } 19}{\text{S } 30}$   
 1951

Dig a circular trench, 5 ft. diam., and raise a flat mound of stone, 2 ft. base, around post.

From this point, the cor. of secs. 19,20,29 and 30 bears S.89°33'E., 42.65 chs. dist., monumented with a lava stone 16x8x6 ins. above ground, set in a small mound of stone, marked with 5 grooves on E. and 2 grooves on S. side.

From the cor. of secs. 19,20,29 and 30, the  $\frac{1}{4}$  sec. cor. of secs. 19 and 20 bears N.0°07'W., 41.78 chs. dist.; monumented with a lava stone, 20x14x8 ins. above ground, set in a small mound of stone and mkd.  $\frac{1}{4}$  on E. side.

From this cor., Pinto Spring reservoir (warm water) bears N.54°39'W., 26.60 chs. dist.