Dependent Resurvey of a portion of the Subdivisional Lines of
T. 29 N., R. 28 E.

Chains	
	S 24 $\frac{1}{4}$ ——— S 25 1949
	Bury the original corner stone alongside the iron post.
	Raise a mound of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, N. of cor.
	Land, rolling and broken hills. Soil, sandy, gravelly and rocky; 4th rate. No timber; undergrowth, sagebrush, shadscale and desert brush.
	SOUTH BOUNDARY OF T. 29 N., R. 28 E.
	Beginning at the remonumented cor. of secs. 35 and 36, on the S. bdy. of the Tp.
	N. 89° 56' W., along the S. bdy. of sec. 35.
	Over rolling and broken general WSW. slope, through dense undergrowth desc. 15 ft.
10.70	Wash, 10 lks. wide, 2 ft. deep, course S. 60° W.; continue descending 30 ft. to $\frac{1}{4}$ sec. cor.
40.00	Point for the $\frac{1}{4}$ sec. cor. of sec. 35.
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.
	$\frac{1}{4}$ S 35 ——— 1949
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
	Desc. gradually 60 ft.
72.40	Main wash, channel, 30 lks. wide with sloping banks 6 ft. high, course winding S. 20° W.; asc. 10 ft.
75.00	Top of ascent; thence desc. 5 ft.
77.90	Wash, 10 lks. wide, 2 ft. deep, course S.; asc. slightly.
80.00	Point for the cor. of secs. 34 and 35.
	Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.
	T29N R28E S34 | S35 ——— S 3 T28N R28E 1949
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
	Land, broken and rolling hills. Soil, sandy, gravelly and rocky; 4th rate. No timber; undergrowth, sagebrush, shadscale and desert brush.