

## INDEPENDENT RESURVEY, 4TH STAN. PAR. S., THROUGH R. 66 E.

Chains	
	West, along the S. bdy. of sec. 31, on a transit line describing the tangent, which bears S. 89° 56.8' W.
	Over rough broken limestone hills, through scattering undergrowth, asc. 40 ft. over general SE. slope.
3.30	Ridge, bears S. 20° W. and N. 20° E.; desc. 230 ft. over NW. slope.
10.90	Draw, drains N.; asc. 90 ft. over NE. slope.
15.30	Spur, slopes N. 10 chs.; desc. 220 ft. over general NW. slope.
30.00	Draw, drains N.; asc. 80 ft. over E. slope.
	Diff. bet. meas. of 40.00 chs., by two sets of chainmen, is nothing.
40.00	N. 22 lks. from the tangent; in saddle of ridge bearing N. and S.,
	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for standard $\frac{1}{4}$ sec. cor., with brass cap mkd.
	SC <u>    S 31</u>
	1938
	raise a mound
	of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
	Descend along low spur sloping W.
50.00	Leave spur, slopes NW. from E.; desc. general W. slope.
63.60	Draw, 150 ft. below $\frac{1}{4}$ sec. cor., drains N.; asc. 30 ft. over E. slope.
65.40	Low spur, slopes N. 20° W.; desc. 25 ft. over general NW. slope.
	Diff. bet. meas. of 80.00 chs., by two sets of chainmen, is nothing.
80.00	N. 26 lks. from the tangent,
	Set an iron post, 3 ft. long, 3 ins. diam., 18 ins. in the ground to solid rock, with a limestone, 8x6x4 ins., mkd. X, deposited at the base, and in a mound of stone to top, for standard cor. of Tps. 16 S., Rs. 65 and 66 E., with brass cap mkd.
	SC T16S R65E      R66E <u>  S36      S31</u>
	1938
	Land, broken limestone hills, changing to rolling desert in W. portion of mile.
	Soil, rocky clay and clay loam; 4th rate.
	Timber, none.
	Undergrowth, creosote brush, mountain rush, and cactus.
	Grazing, poor.