INDEPENDENT RESURVEY, 4TH STAN. PAR. S., THROUGH R. 65 E.

	Chains	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the
	vi dos	ground, with a limestone, 6x4x2 ins., mkd. X, deposited at the base, for standard 4 sec. cor., with brass cap mkd
		SC 4 S 32
		1938
Ĭ.	64.00	Wash, 20 lks. wide, 2 ft. deep, course NE.
		Diff. bet. meas. of 80.00 chs., by two sets of chainmen, is nothing.
	80.00	On the secant,
	•	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with a limestone, 6x4x2 ins., mkd. X, deposited at the base, for standard cor. of secs. 31 and 32, with brass cap mkd.
		sc
		T16S R65E
		S31 S32
*		1938
		of stone, 3 ft. base, 2 ft. high, N. of cor.
	A	Land, nearly level desert; general drainage and exposure
		N. Soil, sandy loam; 3rd and 4th rate. Timber, none. Undergrowth, chaparral, creosote brush, mountain rush, and cactus. Grazing, poor.
		West, along the S. bdy. of sec. 31, on a transit line describing the secant, which bears S. 89° 58.7' W.
		Over rolling desert land, through scattering undergrowth, along a gentle N. slope.
	32.30	Dim road, bears N. 10° W. and S. 10° E.
	33.10	Graded road, bears N. 30° W. to Crystal, and S. 30° E. to Valley of Fire State Park.
		Diff. bet. meas. of 39.50 chs., by two sets of chainmen, is nothing.
	39.50	N. 2 lks. from the secant,
	write.	Set an iron post, 3 ft. long, 1 in. diam., 2 ins. in the ground, for witness standard 4 sec. cor., with brass cap mkd.
· ·	K * 014.	sc
		SC WC _{1/4} S 31
		1938
		of stone, 2 ft. base, $l^{\frac{1}{2}}$ ft. high, N. of cor.
-	40.00	True point for the standard $\frac{1}{4}$ sec. cor. falls in Wash, 20 lks. wide, 5 ft. deep, course N., where it is impractical