INDEPENDENT RESURVEY OF EAST BOUNDARY OF T. 17 S., R. 64 E.

Chains 60.40 Flat wash, 2 chs. wide, course NW. Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, 80.00 for cor. of secs. 7, 12, 13 and 18, with brass cap mkd. T175 R64E R65E S12 , S 7 S13 | S18 1938 raise a mound of stone, 2 ft. base, 12 ft. high, W. of cor. Land, desert; rolling with general NE. slope on S. 10 chs., and nearly level, with gentle NW. slope on remainder of mile. Soil, sandy and gravelly; 3rd rate. Timber, none. Undergrowth, creosote brush, buck brush and cactus. Grazing, poor. North, bet. secs. 7 and 12. Over nearly level desert land, through scattering undergrowth, over a gentle NW. slope. In flat wash, 2 chs. wide, course N.5°W. from SW., 40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for 2 sec. cor., with brass cap mkd. S12 | S 7 1938 raise a mound of stone, 2 ft. base, 12 ft. high, W. of cor. 53.60 Enter wide flat wash, course NE. 67.20 Leave wash; ascend over gentle SE. slope. Intersect the Fourth Standard Parallel South. 69.46 Set an iron post, 3 ft. long, 3 ins. diam., 30 ins. in the ground, for closing cor. of Tps. 17 S., Rs. 64 and 65 E., with brass cap mkd. T16S R64E **S**36 S12 S 7 R64E R65E T175 CC 1938 raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor. From point of intersection, the standard cor. of secs. 35 and 36, T. 16 S., R. 64 E., bears West, 14.16 chs. dist.; an iron post, firmly set, with brass cap marked and witnessed as described in the field notes of the independent resurvey of the Fourth Standard

in. diam., firmly set, with brass cap marked and witnessed as

From the same point, the standard $\frac{1}{4}$ sec. cor., S. bdy. of sec. 35 T. 16 S., R. 64 E., bears East, 25.84 chs. dist.; an iron post, 1

Parallel South executed under this group.