

INDEPENDENT RESURVEY OF WEST BOUNDARY OF T. 17 S., R. 64 E.

Chains

Set an iron post, 3 ft. long, 3 ins. diam., 27 ins. in the ground, for closing cor. of Tps. 17 S., Rs. 63 and 64 E., with brass cap mkd.

T16S R63E

S36

S12 S 7

R63E R64E

T17S

CC

1938

raise a mound

of stone, 3 ft. base, 2 ft. high, S. of cor.

From point of intersection, the standard cor. of secs. 35 and 36, T. 16 S., R. 63 E., bears West, 16.02 chs. dist.; an iron post, 2 ins. diam., firmly set, with brass cap marked and witnessed as described in the field notes of the independent resurvey of the Fourth Standard Parallel South, executed under this group.

From the same point, the standard  $\frac{1}{4}$  sec. cor., S. bdy. of sec. 36, T. 16 S., R. 63 E., bears East, 23.98 chs. dist.; an iron post, 1 in. diam., firmly set, with brass cap marked and witnessed as described in the field notes of the independent resurvey of the Fourth Standard Parallel South, executed under this group.

Land, nearly level desert; general drainage and exposure southerly into Dry Lake.

Soil, varies from clay on S. portion of mile to sandy loam on N. portion; 2nd to 3rd rate.

Timber, none.

Undergrowth, shadscale, creosote brush, mountain rush, and cactus. Grazing, poor.

INDEPENDENT RESURVEY OF SUBDIVISION OF T. 17 S., R. 64 E.

Independent Resurvey superseding the survey executed by R. H. Woods and W. H. Myrick, U. S. Deputy Surveyors, in 1881.

Beginning at the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of T. 17 S., R. 64 E., which is an iron post, 2 ins. diam., firmly set, properly marked, and witnessed as described in the field notes of T. 18 S., R. 64 E., resurveyed under this group.

N.0°01'W. bet. secs. 35 and 36.

Over nearly level desert land, through scattering undergrowth, over a gentle NE. slope.

13.60 Small flat wash, course NE.

32.90 Flat wash, 1 ch. wide, course NE.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to solid rock, with a limestone, 9x6x5 ins., marked X, deposited at the base, and in a mound of stone to top of post, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$

S35 | S36

1938

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 14 ins. in the ground to solid rock, with a limestone, 8x6x4 ins., marked X, deposited at the base, and in a mound of stone to top of post, for cor. of secs. 25, 26, 35 and 36, with brass cap mkd.