INDEPENDENT RESURVEY OF SUBDIVISION OF T. 17 S., R. 64 E.

Chains	Chaine zer de la contra la
	S.89°58'E., on a random line bet. secs. 9 and 16.
40.00	Set temp. 2 sec. weer.
80.14	Intersect N. and S. line, 2 lks. N. of the cor. of secs. 9, 10, 15 and 16.
	Thence
	N.89°57'W., on true line bet. secs. 9 and 16.
	Over nearly level desert land, through scattering undergrowth; descend over a gentle W. slope.
40.07	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a limestone, 6x5x5 ins., marked X, deposited at the base, for the sec. cor., with brass cap mkd.
s e e e	of a formal and a compared to the compared as a compared to the compared to th
	APRIL IN Son of Lorent Lorent Company of the
	.20 25 4 65 ,7 1938 .25 4 65 .27 .25 4 6 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
57.20	Wash, 25 lks. wide, 3 ft. deep, course N.70°W.
80.14	The cor. of secs. 8, 9, 16 and 17.
	Land, nearly level desert; general drainage and exposure W. Soil, sandy; 2nd rate.
	Timber, none. Undergrowth, black brush, creosote brush, and cactus. Grazing, poor.
a minofa	. From a to the tares types a like the every life year.
	N.C°03'W., on a true line bet. secs. 8 and 9.
	Over nearly level desert land, through scattering undergrowth, along a gentle W. slope.
. 4.90	Wash, 25 lks. wide, 2 ft. deep, course 5.80°W.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a limestone, 6x5x4 ins., marked X, deposited at the base, for \$\frac{1}{4}\$ sec. cor., with brass cap mkd.
	de cur t
e =	sg s9
. L. verg e soi , ve	Slope changes gradually to gentle SW. slope.
69.10	Intersect the Fourth Standard Parallel South,
69.10	Intersect the Fourth Standard Parallel South, Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with a limestone, 6x4x3 ins., marked X, deposited at the base, for closing cor. of secs. 8 and 9, with brass cap mkd.
	Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with a limestone, $6x^{1}x^{3}$ ins., marked X, deposited at the base, for closing cor. of secs. 8 and 9, with brass cap mkd. T16S R64E S32
S. C. S.	Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with a limestone, 6x4x3 ins., marked X, deposited at the base, for closing cor. of secs. 8 and 9, with brass cap mkd. T16S R64E S32 S8. S9
o Carbacko	Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with a limestone, $6x^{1}x^{3}$ ins., marked X, deposited at the base, for closing cor. of secs. 8 and 9, with brass cap mkd. T16S R64E S32