

INDEPENDENT RESURVEY OF SUBDIVISION OF T. 17 S., R. 64 E.

Chains

38.06

scattering undergrowth.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

S7

$\frac{1}{4}$

S18

1938

dig pits,

18x18x12 ins., E. and W. of post, 3 ft. dist.

78.06

The cor. of secs. 7, 8, 17 and 18.

Land, nearly level desert with gentle southerly slope.

Soil, clay; 3rd rate.

Timber, none.

Undergrowth, shadscale, buck brush, and creosote brush.

Grazing, poor.

40.00

N.0°03'W., on true line bet. secs. 7 and 8.

Over nearly level desert land with gentle southwesterly slope, through scattering undergrowth.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a quart of charcoal deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$

S7 | S8

1938

68.96

Intersect the Fourth Standard Parallel South,

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with a limestone 4x3x2 ins., marked X, deposited at the base, for closing cor. of secs. 7 and 8, with brass cap mkd.

T16S R64E

S31

S7 | S8

T17S R64E

CC

1938

From the point of intersection the standard corner of T. 16 S., Rs. 63 and 64 E., bears West, 14.08 chs. dist.; an iron post 3 ins. diam., firmly set, marked and witnessed as described in the field notes of the independent resurvey of the Fourth Standard Parallel South, executed under this group.

From the same point the standard $\frac{1}{4}$ sec. cor., S. bdy. of sec. 31, T. 16 S., R. 64 E., bears East, 25.92 chs. dist.; an iron post 1 in. diam., firmly set, marked and witnessed as described in the field notes of the independent resurvey of the Fourth Standard Parallel South, executed under this group.

Land, nearly level desert with a gentle southwesterly slope.

Soil, sandy; 3rd rate.

Timber, none.

Undergrowth, shadscale, buck brush, creosote brush and cactus.

Grazing, poor.