

SURVEY OF PRIVATE CLAIMS IN T. 17 S., R. 64 E.

Chains

South of a railroad tie. This railroad tie was pointed out by John R. Hewitt Jr., present claimant of this land, as the corner of secs. 7, 8, 17 and 18, of the original survey, and the corner from which the tracts in this vicinity had been located. The survey follows the boundaries as indicated on the plat of the survey executed by R. H. Woods and W. H. Myrick, U. S. Deputy Surveyors, in 1881. The tract is not in conflict with any other tract.

At point for the northeast corner of Tract 37,

Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to solid rock, and in a mound of stone to top of post, for angle point No. 1, Tract 37, with brass cap mkd.

T17S R64E

S21

AP 1

TR37

1938

Thence

West, along the N. bdy. of Tract 37.

20.00

Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to solid rock, and in a mound of stone to top of post, for angle point No. 2, Tract 37, and angle point No. 1, Tract 38, with brass cap mkd.

T17S R64E

S21

AP1

AP2

TR38 TR37

1938

Thence

South, along the W. bdy. of Tract 37, identical with the E. bdy. of Tract 38.

20.00

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for angle point No. 3, Tract 37, and angle point No. 4, Tract 38, with brass cap mkd.

TR38 TR37

AP4 | AP 3

S21

T17S R64E

1938

Thence

East, along the S. bdy. of Tract 37.

20.00

Set an iron post, 3 ft. long, 1 in. diam., 11 ins. in the ground to solid rock, and in a mound of stone to top of post, for angle point No. 4, Tract 37, with brass cap mkd.

TR37 T17S

AP4 | R64E

S21

1938