

574

INDEPENDENT RESURVEY OF EAST BOUNDARY OF T. 20 S., R. 64 E.

Chains	
	North, bet. secs. 1 and 6.
	Over broken and rolling desert hills, through scattering undergrowth, descend 30 ft. over NE. slope.
2.20	Wash, 10 lks. wide, 1 ft. deep, course S. 80° E. from N. 60° W.; ascend 60 ft. over S. slope.
7.40	Spur, slopes S. 80° E.; descend 25 ft. over NE. slope.
10.70	Wash, course S. 85° E.; ascend 70 ft. over S. slope.
16.50	Spur, slopes S. 80° E. about 5 chs.; descend 30 ft. over N. slope.
18.30	Wash, 8 lks. wide, 1 ft. deep, drains S. 70° E.; ascend 100 ft. over SE. slope.
21.90	Spur, slopes S. 70° E.; descend 90 ft. over NE. slope.
31.80	Wash, 12 lks. wide, 1 ft. deep, course E.; descend 15 ft. along a general E. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to solid rock, with a sandstone 6x5x2 ins., marked X, deposited at base, and in a mound of stone to top, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.
	 S 1 S 6 1938
47.40	Small wash, course S. 20° E.; ascend S. slope.
51.00	Main drainage divide, 30 ft. above the $\frac{1}{4}$ sec. cor., bears S. 20° E. and N. 20° W.; descend 50 ft. over NE. slope.
52.80	Small wash, course S. 85° E.; ascend 100 ft. over S. slope.
61.50	Spur, slopes S. 40° E.; descend 75 ft. over NE. slope.
64.40	Small wash, course E.; ascend 170 ft. over a general S. slope.
80.50	Divide, bears N. 85° E. and S. 85° W.; descend 50 ft. over N. slope.
84.14	At point of intersection with a line extended East from the cor. of Tps. 19 and 20 S., Rs. 63 and 64 E. Set an iron post, 3 ft. long, 3 ins. diam., 6 ins. in the ground to solid rock, with a limestone, 10x8x3 ins., marked X, deposited at the base, and in a mound of stone to top, for the cor. of Tps. 19 and 20 S., Rs. 64 and 65 E., with brass cap mkd.
	T19S R64E R65E S 36 S 31 ----- S 1 S 6
	T20S 1938
	Land, rolling and broken desert hills; general drainage and exposure SE. on south 80 chs., and N. on remainder of mile. Soil, rocky clay loam, with sandstone, limestone, and