	Chains	
		Independent Resurvey superseding the survey executed by W. H. Myrick, U. S. Deputy Surveyor, in 1882.
		The witness cor. for the stan. cor. of Tps. 20 S., Rs. 65 and 66 E., is an iron post, 3 ins. diam., firmly set, with brass cap mkd., and witnessed as described in the official record.
		Beginning at the true point for the stan. cor. of Tps. 20 S., Rs. 65 and 66 E., which is 3.24 chs. East of the witness cor. for the same.
		Thence
W.		North, bet. secs. 31 and 36, by projection of the meridian established by Polaris observation.
		Over rough broken desert hills, through scattering under growth, ascend rocky broken SW. slope.
	10.00	Slope changes to W.
	23.90	Small draw, drains SW.; asc. SW. slope which changes gradually to W. slope.
	38.60	Ridge, 480 ft. above Tp. cor., bears E. and W., with W. slope; descend 50 ft. along rough broken NW. slope.
	40.00	Set an iron post, 3 ft. long, 1 in. diam., over a X cut in solid surface rock, and in a mound of stone to top, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.
		s36 s31
		1938
		Desc. 75 ft. over a general NW. slope.
	51.00	Wash, 25 lks. wide, 3 ft. deep, course W.; asc. 25 ft. along W. slope.
	54.50	Small draw, drains S. 20° W.; asc. 100 ft. along E. slope.
	63.50	Same draw, drains S. 10° E.; asc. 250 ft. over a general S. slope.
	73.90	Saddle in ridge, bears N. 70° E. and S. 70° W.; desc. 150 ft. over broken NW. slope.
	80.00	True point for the cor. of secs. 25, 30, 31 and 36 falls on sloping shale and limestone ledge where it is impracticable to establish permanent cor. monument.
	80.60	Set an iron post, 3 ft. long, 2 ins. diam., over solid surface rock, and in a mound of stone to top, for the witness cor. to the cor. of secs. 25, 30, 31, and 36, with brass cap mkd.
		R65E R66E S25 S30 S36 S31
	* * *	T20S WC 1938
		from which