14

	Chains	Independent Resurvey superseding the survey executed by W. H. Myrick, U. S. Deputy Surveyor, in 1882.
		From the stan. cor. of secs. 35 and 36, on the S. bdy. of T. 20 S., R. 65 E., which is an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the official record.
		Thence
	- 100 (M)	N. 0° 01' W., bet. secs. 35 and 36.
		Over broken desert hills, through scattering under- growth, ascend 200 ft. over broken SW. slope.
	13.20	Spur, slopes S. 70° W.; thence along W. slope.
	,17.00	Slope changes, descend 280 ft. over steep NW. slope.
	25.50	Enter wash, course S. 60° W.
	28.90	Leave wash; ascend 270 ft. over S. slope.
	40.00	Set an iron post, 3 ft. long, 1 in. diam., on solid surface rock, with a granite stone, $8x6x6$ ins., marked X, deposited at the base, and in a mound of stone to top, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.
		1 07F 07F
		\$35 \$36 1938
	100	Ascend 150 ft. over S. slope.
	47.30	Sharp topped rocky spur, slopes S. 60° W.; thence along
		W. slope.
-	48.80	Spur, slopes N. 80° W.; descend 280 ft. over N. slope.
7.7	57.70	Wash, 15 lks. wide, 3 ft. deep, course N. 70° W.; ascend 125 ft. over broken SW. slope.
	67.40	Spur, slopes N. 50° W.; descend 20 ft. over general NW. slope.
	75.40	Small wash, course S. 80° W.; ascend 100 ft. over SE. slope.
	80.00	Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground to solid rock, with a granite stone, 5x4x4 ins., marked X, deposited at the base, and in a mound of stone to top; for the cor. of secs. 25, 26, 35, and 36, with brass cap mkd.
		T20S R65E S26 S25
		s35 s36 1938
	y	ntibility of frank terming, but an Bibliot of the product the facilities of the franchistics.
		Land, rocky broken desert hills; general drainage and exposure SW.
7.	w. = 1 - 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2 -	Soil, rocky clay loam; 4th rate. Timber, none. Undergrowth, creosote brush, mountain rush, and cactus. Grazing, poor.
-		