

INDEPENDENT RESURVEY OF THE EAST BDY. OF T. 26 S., R. 63 E.

Chains

40.00

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to solid rock and in a large mound of stone, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
 S1 | S6
 1940

raise a mound
of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Desc. 120 ft. over NW. slope.

44.80

Head of ravine, drains NW., continue desc. of broken W. slope.

52.60

Spur, slopes N. 10° W., desc. 200 ft. over broken NE. slope.

63.50

Ravine, drains NW., continue along broken NW. slopes.

80.00

Set an iron post, 3 ft. long, 3 ins. diam., 27 ins. in the ground, for cor. of Ts. 25 and 26 S., Rs. 63 and 64 E., with brass cap mkd.

T25S
 R63E R64E
 S36 | S31
 S 1 | S 6
 T26S
 1940

raise a mound
of stone, 3 ft. base, 2 ft. high, S. of cor.

From this cor., the original twp. cor. bears N. $9^{\circ} 32'$ W., 11.93 dist., a granite rock 18x10x6 ins. mkd. 6 grooves on N. E. S. and W. faces, firmly set, in a mound of stone. I destroy this cor.

Land, hilly.

Soil, gravelly and rocky; 3d and 4th rate.

No timber.

Undergrowth, creosote, black brush, cacti, grasses.

Grazing, fair.

INDEPENDENT RESURVEY OF THE WEST BOUNDARY OF T. 26 S., R. 63 E.

Superseding the survey executed by T. A. Magee in 1882 under Contract No. 142 dated June 21, 1882.

Diligent search was made for each of the original corners along this boundary; no corners were found.

From the cor. of Ts. 26 and 27 S., Rs. 62 and 63 E., which is an iron post, 3 ins. diam., set. mkd. and witnessed as described in the official record; field notes of the resurvey of T. 27 S., R. 63 E.

North, bet. secs. 31 and 36,

Over gently rolling desert land thru medium dense undergrowth.

4.40

Enter dry wash, 60 lks. wide, course generally N. from S. 10° W., continue along bed of wash.

25.00

Leave wash, course N. 10° W.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.