

174

RESURVEY OF S. BDY. T. 23 S., R 63 E.

Chains	
80.00	<p>The cor. of secs. 32, 33, 4, and 5, an iron post, 2 in. diam., set, mkd., and witnessed, as described in the official record. I alter the markings to refer to secs. 32 and 33 only to read as follows:</p> <div><div>T23S R63E</div><div>S32 S33</div><div>T24S R63E</div><div>S5</div><div>1931</div></div> <p>reconstruct mound of stone, 2 ft. base, 1½ ft. high, N. of cor.</p>
40.00	<p>S. 89° 54' W., along S. bdy. sec. 32.</p> <p>The ¼ sec. cor., an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record. I alter the markings to refer to sec. 32 only to read as follows:</p> <div><div>¼ S 32</div><div>1931</div></div>
80.00	<p>The cor. of secs. 5, 6, 31 and 32, an iron post, 2 ins. diam., set, mkd., and witnessed as described in the official record. I alter the markings to refer to secs. 31 and 32 only, to read as follows:</p> <div><div>T23N R63E</div><div>S31 S32</div><div>S6</div><div>T24S</div><div>R63E</div><div>1931</div></div> <p>reconstruct mound of stone, 2 ft. base, 1½ ft. high, N. of cor.</p>
40.00	<p>S. 89° 54' W., along S. bdy. sec. 31.</p> <p>The ¼ cor. of secs. 31 and 6, an iron post, 1 in. diam., set., mkd., and witnessed as described in the official record. I alter the markings to refer to sec. 31 only to read as follows:</p> <div><div>¼ S 31</div><div>1931</div></div>
79.88	<p>The cor. of Ts. 23 and 24 S., Rs. 62 and 63 E., an iron post, 3 ins. diam., set, mkd. and witnessed, as described in the official record. I alter the markings to refer to Ts. 23 S., only to read as follows:</p> <div><div>T23S</div><div>R62E R63E</div><div>S36 S31</div><div>S1</div><div>T24S</div><div>R62E</div><div>1931</div></div> <p>reconstruct mound of stone, 4 ft. base, 3 ft. high, N. of cor.</p>