Chains S. 89° 58' W., along the S. bdy. of sec. 32. Asc. 100 ft. over rolling desert. Point 40.00 chs. in departure from the SE. cor. of sec. 32. 37.18 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for standard \(\frac{1}{4} \) sec. cor., with brass cap mkd. SC 1 S 32 1940 raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor. The original standard 4 sec. cor.; a basalt stone 20x18x18 ins., 40.27 mkd. 4 on N. face and set in a mound of stone. This cor. now becomes an angle point only. Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for angle point, with brass cap mkd. AP T285 R62E S32 1940. Thence, N. 89° 36' W., along the S. bdy. of sec. 32, Asc. 120 ft. over rolling to rocky desert land. Point 80.00 chs. in departure from the SE. cor. of sec. 32. Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for standard cor. of secs. 31 and 32, with brass cap mkd. T285 R62E S31 S32 1940 raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor. Land, rolling and desert hills. Soil, gravelly and rocky; 3rd rate. Timber, joshua trees. Undergrowth, rabbit brush, grass, yucca and other cactus. Grazing, good. N. 89° 36' W., along the S. bdy. of sec. 31. Asc. 30 ft. over rolling desert hills. The original standard cor. of secs. 31 and 32; a basalt stone 3.65 18x10x11 ins., mkd. with 5 grooves on E. face, 1 groove on W. face, set in a mound of stone. This cor. now becomes an angle point only. Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, to bedrock and in a mound of stone to top with the original mkd.

stone deposited at base, for angle point, with brass cap mkd.