

DEPENDENT RESURVEY OF E. BDY. OF T. 28 S., R. 61 E.

Chains

in a mound of stone. This cor. now becomes the cor. of Ts. 27 and 28 S., R. 61 E., only.

Set an iron post, 3 ft. long, 3 ins. diam., 27 ins. in the ground, with the original mkd. stone deposited at base, for cor. of Ts. 27 and 28 S., R. 61 E., with brass cap mkd.

T27S
R61E T28S
S36 R62E
S 6
T28S
S 1
1940

raise a mound
of stone, 2 ft. base, 1½ ft. high, W. of cor.

From this cor., the cor. of Ts. 27 and 28 S., R. 62 E., only, bears North, 3.38 chs. dist.

Land, rolling.
Soil, sandy and gravelly; 3rd rate.
Timber; joshua trees.
Undergrowth; black brush and native grass.
Grazing, good.

INDEPENDENT RESURVEY OF THE N. BDY. OF T. 28 S., R. 62 E.

Superseding the survey executed by W. H. Myrick, Deputy Surveyor, in 1883 and 1884.

Begin the resurvey at the cor. of Ts. 27 and 28 S., Rs. 62 and 63 E.; an iron post, 3 ins. diam., set, mkd. and witnessed as described in the field notes of the dependent resurvey of T. 28 S., R. 63 E., this same group.

West, bet. secs. 1 and 36, on a transit line describing the tangent, which bears S. 89° 59.4' W.
Over desert hills.

- 8.00 Low spur, slopes S.; desc. 70 ft. over SW. slope.
- 17.00 Wash, course SE.; asc. 90 ft. over general E. slope.
- 34.30 Minor wash, course NE.; asc. 30 ft. over NE. slope.
- 38.70 Low spur, slopes NE.; desc. 20 ft. over NW. slope.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for ¼ sec. cor., with brass cap mkd.

S 36
¼
S 1
1940

raise a mound
of stone, 2 ft. base, 1½ ft. high, N. of cor.

The original ¼ sec. cor.; a basalt stone, 14x14x4 ins., mkd. ¼ on N. face, set in a mound of stone, bears S. 5° 15' E., 3.88 chs. dist. I destroy this cor.

- 40.60 Minor wash, course NE.; asc. 20 ft. over NE. slope.
- 44.80 Dim road, bears NE. and SW.
- 47.10 Low ridge, bears NW. and SE.; desc. 40 ft. over SW. slope.
- 59.20 Wash, course SE.; over low rolling hills.