

## INDEPENDENT RESURVEY OF SUBDIVISION, T. 28 S., R. 62 E.

Chains

S 6	
23	22
6	5
S 7	
1940	

- 86.40 Dim road, bears NW. and SE.
- 90.30 Wash, course SE.
- 91.53 Intersect the W. bdy. of the township.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with a granite stone, 8x5x4 ins., mkd. X, deposited at base, for closing cor. of secs. 6 and 7, with brass cap mkd.

T28S	
R61E	R62E
S 12	S 6
S 7	
1940	

The cor. of secs. 1 and 12 bears N. 0° 33' W., 3.15 chs. dist.

Land, rolling.

Soil, sandy and gravelly; 3rd rate.

Timber, joshua trees.

Undergrowth, black brush and creosote brush.

Grazing, good.

At midpoint on the W. bdy. of sec. 7,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

	$\frac{1}{4}$ S 7
1940	

raise a mound  
of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, E. of cor.

The  $\frac{1}{4}$  sec. cor. of sec. 12 bears N. 0° 28' W., 2.335 lks. dist.

At point 40.00 chs. in latitude from the closing cor. of secs. 6 and 7, on W. bdy. Sec. 6.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

	$\frac{1}{4}$ S 6
1940	

raise a mound  
of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, E. of cor.

The  $\frac{1}{4}$  sec. cor. of sec. 1 bears N. 0° 47' W., 4.11 chs. dist.

At point 80.00 chs. in latitude from the closing cor. of secs. 6 and 7, on W. bdy. Sec. 6.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a granite stone 7x5x4 ins., mkd. X, deposited at base, for lot cor., with brass cap mkd.