

## INDEPENDENT RESURVEY OF THE SUBDIVISION OF T. 27 S., R. 63 E.

Chains	
52.00	Wash, drains N.; asc. 170 ft. over E. slope.
60.30	Spur, slopes N.10°W.; desc. 70 ft. over broken NW. slope.
65.90	Draw, drains N.
68.60	Spur, slopes N.5°W. from S.20°E.; desc. 140 ft. over W. slope.
81.00	Draw drains N.30°W.
81.19	Intersect the W. bdy. of Tp.
	The point of intersection falls on edge of draw where it is impracticable to establish a permanent corner. Therefore, at a point West, 10 lks. dist.,
	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for witness closing cor. of secs. 30 and 31, with brass cap mkd.
	T27S R62E   R63E   S30 S 36   S31 CC WC   1940
	raise a mound
	of stone, 3 ft. base, 2 ft. high, E. of cor.
	From the true point for the closing cor., the cor. of secs. 25 and 36, T. 27 S., R. 62 E. bears N., 1.40 chs. dist.
	Land, broken mountainous and hilly. Soil, shallow, coarse, rocky, 3d and 4th rate. No timber. Undergrowth, creosote, black brush, cacti, grasses. Grazing, fair.
	From the cor. of secs. 29, 30, 31 and 32, N.0°03'W., bet. secs. 29 and 30, Over broken hilly land through medium dense undergrowth. Desc. 100 ft. over broken N. slope.
8.40	Draw, drains N.65°W.; asc. 60 ft. along broken SW. slope.
12.60	Top of ascent; desc. along broken W. slope.
17.50	Slope changes to rocky S.; asc. 110 ft.
27.60	Spur, slopes S.80°W.
30.60	Head of small draw, drains NW.
34.80	Rocky spur, slopes NW.; desc. 60 ft. over NE. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., over a cross X cut on exposed ledgerrock, and in a large mound of stone, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S30   S29 1940
	Continue descent of broken N. slope 170 ft.
49.90	Draw, drains NE.; continue along broken NE. slope.
63.00	Draw, drains E.; asc. 220 ft. over rocky SE. slope.