

DEPENDENT RESURVEY OF 7TH STAN. PAR. S0 THROUGH R. 63 E.

Chains
80.64

The original standard cor. of secs. 31 and 32, a squared wooden stake, 30x2x2 ins. mkd. SC on S. face, S I on NW. face, and illegible scribe marks on NE. face.

At cor. point,

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with the original corner stake alongside, for standard cor. of secs. 31 and 32, with brass cap mkd.

SC
T28S R63E
S31 | S32

1939

raise a mound

of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

Land, slightly rolling desert; general drainage and exposure S.

Soil, sandy; 3rd rate.

Timber, scattered joshua trees.

Undergrowth, creosote brush, yellow top, cactus and yucca.

Grazing, fair.

N. 89° 23' W., along the S. bdy. of sec. 31,

Over slightly rolling desert land, through scattering joshua trees and medium dense undergrowth.

16.20 Wash, 30 lks. wide, 2 ft. deep, course SE.

37.50 Small wash, course SE.

40.30 Proportionate distance; no evidence of original cor. could be found.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for standard $\frac{1}{4}$ sec. cor., with brass cap mkd.

SC
 $\frac{1}{4}$ S31

1939

raise a mound

of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

52.10 Small wash, course S. 30° E.

68.30 Wash, 30 lks. wide, 2 ft. deep, course SE.

80.60 The standard cor. of T. 28 S., Rs. 62 and 63 E., a porphyry stone, 12x8x3 ins., mkd. 6 grooves on the E., W. and N. faces.

At cor. point,

Set an iron post, 3 ft. long, 3 ins. diam., 27 ins. in the ground, with the original corner stone deposited at the base, for standard cor. of T. 28 S., Rs. 62 and 63 E., with brass cap mkd.

SC
T28S
R62E R63E
S36 | S31

1939

raise a mound

of stone, $3\frac{1}{2}$ ft. base, 2 ft. high, N. of cor.

Land, slightly rolling desert; general drainage and exposure SE.

Soil, sandy and gravelly; 3rd rate.