Dependent Resurvey of T. 32 S., R. 66 E., M. D. M.

	Dependent head vey of 1. % b., h. oo 2., m.
Chains	
79.86	The corner of secs. 1, 2, 35 and 36, marked by the 1932 resurvey monument, an iron post, 2 ins. diam., firmly set and marked and witnessed as described in the official record.
	Land, level bench and broken mountainous. Soil, sandy, gravelly and rocky; 3rd and 4th rate.
	Timber, none. Undergrowth, creosote brush and cactus. Grazing, poor.
	The point for the N. $\frac{1}{4}$ sec. cor. of sec. 1 is at proportionate distance on the north boundary of the section.
	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd.
	1/4 S1 ·
	1947
	Raise a mound of stone, 2 ft. base, $l_2^{\frac{1}{2}}$ ft. high, S. of cor.
	From this cor. the witness meander cor. of secs. 1 and 36 bears East 3.99 chs. dist.
	From the corner of secs. 22, 23, 26 and 27.
	N.Oo 34' W., bet. secs. 22 and 23.
	Over gently rolling bench land.
33.00	Unimproved road, bears N. 30° E., and S. 30° W.
40.30	The $\frac{1}{4}$ sec. cor. of secs. 22 and 23, marked by the original monument, an old mound of earth witnessed by traces of old pits E. and W. of cor
	At the corner point
	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd.
	$\frac{1}{4}$
	S22 S23
	·
	1947
	Dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist.
	N. 1º 15' E., bet. secs. 22 and 23, beginning new measurement.
	Desc. slightly over gently rolling land.
40.95	The corner of secs. 14, 15, 22 and 23, marked by the original monument, a granite stone, 6x12x14 ins., mkd. with 3 grooves on the south face and 2 grooves on the east face, loosely set in a mound of stone.
	At the corner point
	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with brass cap mkd.
	T32S R66E S15 S14
	S22 S23
	1947
	Raise a mound of stone, 2 ft. base, $l_{\frac{1}{2}}$ ft. high, W. of cor. and bury the original marked stone at the base of the iron post.
	I and gently welling

Land, gently rolling.