

Dependent Resurvey of the Sixth Standard Parallel North
along the South Boundary of T. 31 N., R. 66 E.

Chains 22.00	Road, bears N. 60° W. and S. 60° E.
40.16	Proportionate point Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for standard $\frac{1}{4}$ sec. cor., with brass cap mkd. <u>SC</u> <u>$\frac{1}{4}$ S35</u> 1939 of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor. raise a mound
80.32	The original standard cor. of secs. 35 and 36, a juniper post, 2 ins. square, 26 ins. long, with illegible scribe marks. At point for corner Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with the original post deposited at base, for standard cor. of secs. 35 and 36, with brass cap mkd. <u>SC</u> <u>T31N R66E</u> <u>S35 S36</u> 1939 of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor. raise a mound Land, level. Soil, sandy loam; 3rd rate. Timber, none. Undergrowth, shadscale and sagebrush. Grazing, fair.
40.16	S. 88° 34' E., along the S. bdy. of sec. 36. Over level land. Proportionate point Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for standard $\frac{1}{4}$ sec. cor., with brass cap mkd. <u>SC</u> <u>$\frac{1}{4}$ S36</u> 1939 of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor. raise a mound
43.00	Road, bears S. 70° E. and N. 70° W.
80.32	The standard cor. of Tps. 31 N., Rs. 66 and 67 E., a juniper post, 2 ins. square, 26 ins. long, with illegible scribe marks. At point for corner