

Dependent Resurvey of the Sixth Standard Parallel North
along the South Boundary of T. 31 N., R. 67 E.

Chains	
27.10	Road, bears N. 20° E. and S. 20° W.
39.94	Proportionate point Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a limestone, 2x4x4 ins., mkd. with a cross (X), deposited at base, for standard $\frac{1}{4}$ sec. cor., with brass cap mkd. <div style="text-align: center;"> SC <u>$\frac{1}{4}$ S35</u> 1939. </div> No suitable accessory
54.70	Road, bears N. 10° E. and S. 10° W.; asc. 150 ft. over W. slope.
79.88	Proportionate point for standard cor. of secs. 35 and 36 falls on sloping surface rock where it is impractical to establish a permanent corner monument. Land, level and rolling. Soil, sandy and gravelly clay; 3rd rate. Timber, none. Undergrowth, shadscale and white sage. Grazing, fair.
	S. 88° 43' E., along the S. bdy. of sec. 36.
0.10	Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground to bedrock and in a mound of stone to top, for witness standard cor. of secs. 35 and 36, with brass cap mkd. <div style="text-align: center;"> SC T31N R67E <u>S35 S36</u> WC </div> 1939 Asc. 350 ft. over W. slope.
20.00	Minor drain, course S. 70° W.; asc. 400 ft. over SW. slope.
39.94	Proportionate point Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bedrock and in a mound of stone to top, for standard $\frac{1}{4}$ sec. cor., with brass cap mkd. <div style="text-align: center;"> SC <u>$\frac{1}{4}$ S36</u> 1939 </div> <div style="text-align: right;">from which</div> A pine, 18 ins. diam., bears N. 28° E., 18 lks. dist., mkd. $\frac{1}{4}$ S36 SCBT A pine, 15 ins. diam., bears N. 86 $\frac{1}{2}$ ° W., 68 lks. dist., mkd. $\frac{1}{4}$ S36 SCBT. Asc. 100 ft. over SW. slope.