

Dependent Resurvey of the Sixth Standard Parallel North
along the South Boundary of T. 31 N., R. 67 E.

Chains	
43.60	Spur, projects N. 60° W.; desc. 40 ft. along N. slope.
51.00	Asc. 50 ft. over NW. slope.
55.50	Spur, projects N. 10° W.; desc. 40 ft. over NE. slope.
58.50	Asc. 150 ft. over NW. slope.
67.00	Spur, projects N. 30° W.; desc. slightly along N. slope.
75.00	Asc. 200 ft. over NW. slope.
79.88	The standard cor. of Tps. 31 N., Rs. 67 and 68 E., an iron post, 3 ins. diam., set, mkd. and witnessed as described in the field notes of the resurvey of the Sixth Standard Parallel North, through Range 68 East.
	Land, mountainous.
	Soil, gravelly clay; 3rd rate.
	Timber, pine and juniper.
	Undergrowth, sagebrush.
	Grazing, fair.

Dependent Resurvey of the East Boundary of
T. 31 N., R. 66 E.

Reestablishment of surveys executed by Smyles and Preble,
Deputy Surveyors, in 1881.

From the standard cor. of Tps. 31 N., Rs. 66 and 67 E.
N. 0° 19' E., bet. secs. 31 and 36.

Over level land.

39.80 Proportionate point

set an iron post, 3 ft. long, 1 in. diam., 27 ins. in
the ground, with a glass jar deposited at base, for $\frac{1}{4}$
sec. cor., with brass cap mkd.

$\frac{1}{4}$

S36 | S31

1939

No suitable accessory

79.60 Proportionate point

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in
the ground, for cor. of secs. 25, 30, 31 and 36, with
brass cap mkd.

T31N
R66E R67E
S25 | S30
S36 | S31

1939

raise a mound
of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.