

Dependent Resurvey of the North Boundary of
T. 32 N., R. 67 E.

25

Chains

N. 88° 45' E., bet. secs. 1 and 36.

Over rolling land.

7.50 Road, bears N. 5° E. and S. 5° W.

29.00 Road, bears S. 85° E. and N. 80° W.

32.00 Road, bears N. 85° E. and S. 85° W.

40.01 Proportionate point

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to underlying rock, with a brick mkd. with a cross (X), deposited at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{1}{4} \frac{S36}{S1}$$

1939

Asc. 250 ft. over rolling W. slope.

80.02 The cor. of Tps. 32 and 33 N., R. 67 E., an iron post, 3 ins. diam., set, mkd. and witnessed as described in the field notes of the resurvey of the East Boundary of T. 32 N., R. 67 E.

Land, rolling.

Soil, clay and gravelly; 3rd rate.

Timber, none.

Undergrowth, sagebrush and white sage.

Grazing, fair.

Dependent Resurvey of the West Boundary of
T. 31 N., R. 66 E.

Reestablishment of surveys executed by Smyles and Preble,
Deputy Surveyors, in 1881.

From the standard cor. of Tps. 31 N., Rs. 65 and 66 E.

N. 0° 53' E., bet. secs. 31 and 36.

Over nearly level land.

40.19 Proportionate point

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{1}{4}$$

$$S36 | S31$$

1939

of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. raise a mound

80.38 The original cor. of secs. 25, 30, 31 and 36, a juniper post, 2 ins. square, 2 ft. long, mkd. with 1 notch on S. edge and 5 notches on N. edge.