

Dependent Resurvey of the North Boundary of T. 4 S., R. 60 E.

Chains

West, along the N. bdy. of sec. 3.
Over rolling bench, through medium dense undergrowth.

39.66

Point for the $\frac{1}{4}$ sec. cor. of sec. 34, T. 3 S., R. 60 E.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground and in a mound of stone, with brass cap mkd.

T3S R60E

 $\frac{1}{4}$ S34

1958

40.28

The original $\frac{1}{4}$ sec. cor. of secs. 3 and 34, Ts. 3 and 4 S., R. 60 E. mkd. by a limestone, 18x10x4 ins., firmly set in the ground and in a mound of stone, mkd. $\frac{1}{4}$ on N. face.

At the same point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground and in a mound of stone, with brass cap mkd.

 $\frac{1}{4}$ S3

T4S R60E

1958

Deposit the original stone alongside the post.

Thence

West, beginning new measurement.

39.38

Point for the cor. of secs. 33 and 34, T. 3 S., R. 60 E.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground to solid rock, and in a mound of stone, with brass cap mkd.

T3S R60E

S33 | S34

S 3.00

T4S

1958

Deposit broken glass at base of post.

40.29

The original cor. of secs. 3, 4, 33 and 34, Ts. 3 and 4 S., R. 60 E. mkd. by a limestone 24x8x6 ins., firmly set in the ground and in a mound of stone, mkd. with 3 notches on E. and W. corners.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 17 ins. in the ground to solid rock, and in a mound of stone, with brass cap mkd.

T3S R60E

S33

S4 | S3

T4S

1958

Deposit the original stone alongside the iron post.