

Islands in Sec. 16, T. 19 N., R. 19 E., M.D.M.

Chains

from which the cor. of secs. 9, 10, 15 and 16, bears N. $38^{\circ} 39'$ E.,
9.99 chs. dist. by calculation.

Thence

N. $50^{\circ} 00'$ W.

0.64

The SE. bank of island at ordinary high water elevation.

Point for the auxiliary meander cor. of the island designated
Lot 10.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground,
with brass cap mkd.

AMC
T19N R19E
S 16
LOT 10

1949

from which the cor. of secs. 9, 10, 15 and 16 bears N. $42^{\circ} 19'$ E.,
10.00 chs. dist. by calculation.

Thence

N. $57^{\circ} 41'$ W.

2.54

The bank of east end of island at ordinary high water elevation.

Point for the auxiliary meander cor. of island designated Lot 12.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground,
with brass cap mkd.

AMC
T19N R19E
S 16
LOT 12

1949

from which

A concrete cylinder, 9 in. diam., top flush with the surface
of the ground, bears S. $36^{\circ} W.$, 0.08 chs. dist.

The sec. cor. bears N. $55^{\circ} 47'$ E., 10.73 chs. dist. by
calculation.

Survey of the Island Designated Lot 10

Beginning at the auxiliary meander cor.

Thence with the meanders of the island.

Along top of bank 2 to 4 ft. high.

N. $74^{\circ} 15'$ E., 1.10 chs.

N. $77^{\circ} 00'$ W., 1.70 chs.

N. $82^{\circ} 00'$ W., 1.00 ch.

S. $18^{\circ} 15'$ W., 0.60 chs.

S. $16^{\circ} 00'$ W., 1.00 ch.