

Dependent Resurvey of the First Standard Parallel South,
Along the South Boundary of Section 36, T. 4 S., R. 61 E.

Chains

Thence

N. 89° 41' E., on the First Standard Parallel South, along the south boundary of sec. 36, T. 4 S., R. 61 E.

Over nearly level desert valley, sloping very gradually to W., through scattered undergrowth; asc. 125 ft. to the $\frac{1}{4}$ sec. cor.

27.40 Unimproved dirt road, bears N. 20° E. and S. 20° W.

39.99 Point for the standard $\frac{1}{4}$ sec. cor. of sec. 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a mound of stone, 2 $\frac{1}{2}$ ft. base, 10 ins. high, with brass cap mkd.

S C
 $\frac{1}{4}$ S 36

1953

Dig a circular trench, 5 ft. diam., 1 ft. deep, around the iron post.

Asc. 125 ft. over very gradual W. slope to township corner.

75.93 Point for the closing cor. of Ts. 5 S., Rs. 61 and 62 E., hereinafter described.

79.98 The original standard cor. of Ts. 4 S., Rs. 61 and 62 E., which is monumented with a weathered lava stone, 20x11x6 ins., firmly set in old flat mound of earth, and bearing illegible markings on E., W., and N. faces.

At the corner point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 28 ins. in the ground, with brass cap mkd.

S C
T4S
R61E R62E
S36 | S31

1953

Deposit the old corner stone alongside; dig a surrounding circular trench, 5 ft. diam., 1 ft. deep; and raise a flat mound of earth around the iron post.

Land, nearly level desert valley.

Soil, light colored alkaline sandy clay loam.

Timber, none; undergrowth, sparse sagebrush and greasewood.

Independent Resurvey of the East Boundary of T. 5 S., R. 61 E.

Superseding the Survey Executed by
E. B. Monroe, Deputy Surveyor, in 1870.