

Independent Resurvey of the East Boundary of T. 5 S., R. 61 E.

Chains

40.00

Point for the E. $\frac{1}{4}$ sec. cor. of sec. 12.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground to solid rock, and in a mound of stone, 4 ft. base, 14 ins. high, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ | \\ \text{S } 12 \\ | \\ 1953 \end{array}$$

from which

A point on top face of a rock outcrop, 15x10x8 ft. above ground, bears South, 10 lks. dist., mkd. B+O.

Corner is situated in pocket among large boulders and rock outcroppings.

Asc. 310 ft. over steep, rocky SW. slope strewn with numerous large boulders.

57.00

Spur ridge, bears N. 60° W. and S. 60° E.; desc. 565 ft. over NE. slope.

75.80

Wash, 80 lks. wide, 3 ft. deep, in canyon, which drains W. from SE.; asc. 100 ft. over SW. slope of boulder strewn hillside.

79.925

A safe place for reference monument to secs. 1 and 12.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., over an "X" mkd. on barren bedrock, and supported in a mound of stone, $4\frac{1}{2}$ ft. base, 30 ins. high, with brass cap mkd.

$$\begin{array}{c} \text{R M} \\ \text{T5S} \\ \hline \text{S1} \\ \hline \text{S12} \\ \hline \text{R61E} \end{array} \begin{array}{c} | \\ \text{T5S} \\ \hline \text{R62E} \\ \hline \text{S6} \end{array}$$

1953

from which

A pinon, 5 ins. diam., bears S. 16° W., 50 lks. dist., mkd. S12 BT only.

A point on SE. face of rock outcrop protruding 15x15x10 ft. above ground, bears N. 77° W., 24 lks. dist., mkd. B+O.

80.00

Point for cor. of secs. 1 and 12, falls on face of steep sloping rock outcropping, in impractical position for corner monument. I mark the corner point by a hole 6 ins. deep drilled slantwise, at right angle to the surface into the rock.

Land, broken and mountainous.

Soil, sandy to rocky clay loam.

Timber, scattered juniper and pinon; undergrowth, sagebrush, greasewood, blackbrush, and bunch grass.

North, on E. bdy. of sec. 1.