

Survey of the North Boundary of T. 7 S., R. 62 E.

Chains

Dig a surrounding circular trench, 6 ft. diam., 1 ft. deep, and raise a flat mound of earth around the iron post.

56.00 Wash, 3 chs. wide, 4 ft. deep, course SSW.; asc. 60 ft. over gradual E. slope to sec. cor.

70.20 Bladed dirt road, bears N. 15° W. and S. 15° E.

80.00 Point for the cor. of secs. 5, 6, 31 and 32.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T6S	R62E
S31	S32
S6	S5
T7S	
1953	

Dig a surrounding trench, 6 ft. diam., 1 ft. deep, and raise a flat mound of earth around the iron post.

Land, nearly level to gently rolling desert valley.

Soil, sandy clay loam.

Timber, scattered Joshua trees; undergrowth, greasewood and sagebrush.

West, bet. secs. 6 and 31, on a latitudinal curve.

Over gently sloping desert valley land, through scattered timber and undergrowth; asc. 190 ft. over gradual E. slope to ¼ sec. cor.

6.75 Dim unimproved dirt road, bears N. 50° E. and S. 50° W.

9.26 Four strand barbed wire fence, constructed and maintained by the Bureau of Land Management, bears N. 68½° E. and S. 68½° W.

9.50 Unimproved service road, parallels fence.

39.00 Begin ascent of E. slope of mountain, leaving desert valley, bears N. and S.

40.00 Point for the ¼ sec. cor. of secs. 6 and 31.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

¼	S 31
	S 6
1953	

Raise a mound of stone, 3½ ft. base, 6 ins. high, around the iron post.

No auxiliary accessory.

Asc. 710 ft. over rough, broken, mountainous E. slope.

66.80 Narrow crested ridge divide, bears N. 10° E. and S.; desc. 90 ft. over W. slope to W. bdy. of the township.

70.72 Intersect the E. bdy. of sec. 36, T. 6 S., R. 61 E.

Point for closing cor. of Ts. 6 and 7 S., R. 62 E.