

176

Independent Resurvey of the Second Standard Parallel South,  
Along a Portion of the South Boundary of T. 8 S., R. 62 E.

Chains

This cor. will no longer serve as the SE. cor. of sec. 36, but becomes an angle point in the S. bdy. of sec. 36 as located in terms of the present independent resurvey; I alter the markings of the brass cap so that it now reads

A P  
T8S R62E  
S 36

1952

N. 89° 55' W., continuing measurement.

10.73

The original closing cor. of Ts. 9 S., Rs. 62 and 63 E., which is monumented with an iron post, 3 ins. diam., firmly set, marked and witnessed as described in the official record. I add the date "1952" to the old markings.

40.00

Point for the standard  $\frac{1}{4}$  sec. cor. of sec. 36.

Using the iron post from the 1916 resurvey standard  $\frac{1}{4}$  sec. cor. of sec. 36, which is 3 ft. long, 1 in. diam., I set it 26 ins. in the ground, and in a flat mound of stone, 2 ft. diam., with brass cap now mkd.

S C  
 $\frac{1}{4}$  S 36

1952

Raise a mound of stone,  $3\frac{1}{2}$  ft. base, 2 ft. high, N. of cor.

From this corner, the point for the 1916 resurvey standard  $\frac{1}{4}$  sec. cor. of sec. 36, from which I removed the above iron post, bears N. 89° 55' W., 3.21 chs. dist. I destroy all visible evidence of the old corner position and its accessories.

Desc. 110 ft. over W. slope.

46.00

Ravine, drains N.; asc. 330 ft. over a general NE. slope.

67.40

Spur, slopes NE.; desc. 140 ft. over NW. slope.

80.00

Point for the standard cor. of secs. 35 and 36.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

S C  
T8S R62E  
S35|S36

1952

Raise a mound of stone,  $3\frac{1}{2}$  ft. base, 2 ft. high, N. of cor.

Land, rolling hills and mountains.

Soil, clay, gravel and rock.

Timber, scattered Joshua trees; undergrowth, sagebrush, greasewood and cacti.

N. 89° 55' W., on the S. bdy. of sec. 35.

Over rolling to broken desert hills; desc. 40 ft. over NW. slope.