

Independent Resurvey of the Second Standard Parallel South,
Along the South Boundary of T. 8 S., R. 63 E.

Chains

S C
T8S R63E
S31 | S32

1952

No auxiliary accessory.

From this corner, the point for the original standard cor. of secs. 31 and 32, from which I removed the above iron post, bears N. 57° 45' W., 4.03 chs. dist. I destroy all visible evidence of the original corner position and its accessories.

Land, mountainous.

Soil, clay, rock, and gravel.

Timber, scattered juniper and Joshua trees; undergrowth, sagebrush, greasewood, and cacti.

N. 89° 59' W., along the S. bdy. of sec. 31, along a rhumb line.

Over mountainous land, through scattered Joshua trees and medium dense undergrowth; desc. 300 ft. over steep NW. slope.

8.50 Wash, 10 lks. wide, 2 ft. deep, drains N. 70° W.; desc. 55 ft. along steep N. slope.

16.50 Ledge, bears N. and S.; desc. 325 ft. over abrupt W. and NW. slopes.

38.70 Low saddle in divide ridge, which bears N. 60° W. and S. 60° E.; thence along S. slope.

40.00 Point for the standard $\frac{1}{4}$ sec. cor. of sec. 31.

Using the iron post from the original standard $\frac{1}{4}$ sec. cor. of sec. 31, which is 3 ft. long, 1 in. diam., I set it 8 ins. in the ground to bedrock, and in a supporting mound of stone, 4 ft. base, 28 ins. high, with brass cap now mkd.

S C
 $\frac{1}{4}$ S 31

1952

No auxiliary accessory.

From this corner, the point for the original standard $\frac{1}{4}$ sec. cor. of sec. 31, from which I removed the above iron post, bears N. 58° 30' W., 4.02 chs. dist. I destroy all visible evidence of the old corner position and its accessories.

Continue along S. slope.

43.50 Change to SE. slope; asc. 35 ft. over same.

47.50 Spur, slopes S. 20° W.; desc. 420 ft. over abrupt W. slope.

60.00 Rocky side spur, falls S. 70° W.; desc. 220 ft. over SW. slope.

68.90 Wash, 15 lks. wide, 2 ft. deep, drains N. 20° W.; asc. 35 ft. along a N. slope.

73.00 Spur, slopes N. 30° W.; desc. 40 ft. along broken N. slope to the township corner.